

Factory Five '35 Hot Rod Truck (Model 93034-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
5105	Ball bearings, blue rubber sealed (6x10x3mm) (2)
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
	Body & Accessories
335	Body, Factory Five '35 Hot Rod Truck (clear, requires painting)/
	foam pads (front)/ decal sheet (includes front grille, side mirrors,
	headlights, tail lights, mounting hardware)
9335X	Body, Factory Five '35 Hot Rod Truck, complete (graphite) (painted,
	decals applied) (includes front grille, side mirrors, headlights, tail
2250	lights, foam pads)
335R	Body, Factory Five '35 Hot Rod Truck, complete (red) (painted, decals applied) (includes front grille, side mirrors, headlights, tail
	lights, foam pads)
9337	Grille, Factory Five '35 Hot Rod Truck/ grille mount/ 2.6x8 BCS (5)
334	Headlight housings (left & right)/ headlight lens (2)/ 2.6x8 BCS (2)/
	1.6x7 BCS (self-tapping) (2) (fits #9333 or 9335 body)
9339	Side mirrors (left & right)/ mounts (2)/ tail light lens (2)/ retainers (2)/
	1.6x7 BCS (self-tapping) (6) (fits #9333 or 9335 body)
	Brake Components
3367	Brake calipers (red), front (2)/ rear (2)
3356	Wheel hubs, hex (disc brake rotors) (4)
001	
3381	Housing, differential (front)
3380	Housing, differential (rear)
	Chassis & Attachments
9324	Battery hold-down/ battery clip/ hold-down post/ screw pin/ piv ot post
	screw/ foam spacer (for 300mm wheelbase)
3315	Body mounts, front & rear (2)
317	Body washers, foam
3924	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10
322	CS (2)/ 3x15 CCS (3) Chassis (for 300mm wheelbase)
322	Chassis brace (front)
323	Gear cover (rear chassis brace)/ wire retainer
9338	Shock towers, front & rear
323	Skidplate, front/ serv o mounts, steering (2)
	Differential Components
5381	Carrier, differential/x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5136X	Differential oil kit (50cc of 1 each: 10K, 30K, 50K weights)
381	Housing, differential (front)
380	Housing, differential (rear)
379 879P	Housing, spool / spool shaft/ bushing Ring gear, differential/ ninion gear, differential/machined, spiral
6879R	Ring gear, differential/ pinion gear, differential (machined, spiral cut) (rear)
879	Ring gear, differential/ pinion gear, differential (rear)
	Driveline Components
353X	Drive cups, inner (2) (steel constant-velocity driveshafts)/ screw
ACCC	pins (2)
3353	Drive cups, inner (2)/ screw pins (2)
356	Driv eshaft, center, steel (278mm)/ pin/ support, center driv eshaft/
	5x11x4 bearing
350	Driveshaft, front (2)
351	Driv eshaft, rear (2)
	Driveshafts, steel constant-velocity (assembled), front (2)
	Driveshafts, steel constant-velocity (assembled), rear (2)
351X	$O_{\rm min}$ and (40)
3351X 3382	O-rings (12)
3351X 3382 2754	Stub axle pins (4)
3351X 3382 2754 3354	Stub axle pins (4) Stub axles (front or rear) (2)
3351X 3382 2754 3354	Stub axle pins (4) Stub axles (front or rear) (2) Wheel hubs, hex (disc brake rotors) (4)
3350X 3351X 3382 2754 3354 3356	Stub axle pins (4) Stub axles (front or rear) (2)
3 351X 3382 2754 3354 3356	Stub axle pins (4) Stub axles (front or rear) (2) Wheel hubs, hex (disc brake rotors) (4)
3351X 3382 2754 3354	Stub axle pins (4) Stub axles (front or rear) (2) Wheel hubs, hex (disc brake rotors) (4) Front Suspension & Steering
3351X 3382 2754 3354 3356 3330 3341 3332	Stub axle pins (4) Stub axles (front or rear) (2) Wheel hubs, hex (disc brake rotors) (4) Fromt Suspension & Steering Bulkhead, front Camber link/toe link set (plastic/ non-adjustable) (front & rear) Caster blocks (c-hubs) (2)/ kingpin bushings (4)
3351X 3382 2754 3354 3356 3330	Stub axle pins (4) Stub axles (front or rear) (2) Wheel hubs, hex (disc brake rotors) (4) Front Suspension & Steering Bulkhead, front Camber link/toe link set (plastic/ non-adjustable) (front & rear)

• ·	-
334G	Mounts, suspension arms, aluminum (green-anodized) (front & rear)/ hinge pin retainers (12)/ inserts (6)
334R	Mounts, suspension arms, aluminum (red-anodized) (front & rear)/ hinge pin retainers (12)/ inserts (6)
985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)
345	Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1))
345G	Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1),
345R	(1)) Serve sever puts aluminum red anodized (box (1) serrated (1))
	Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1))
344	Serv o sav er/ serv o sav er spring/ serv o horn, steering
343	Steering bellcranks/ hardware
3337	Steering block (2)
2754	Stub axle pins (4)
354	Stub axles (front or rear) (2)
0330	Suspension arms, front (2)
340	Suspension pin set, complete (front & rear)
342	Toe links, steel (34mm) (2)
341X	Turnbuckles, aluminum (blue-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/
2410	aluminum wrench Turnbucklos, aluminum (groon, anodized), camber links, 32mm
341G	Turnbuckles, aluminum (green-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
341R	Turnbuckles, aluminum (red-anodized), camber links, 32mm
5 4 IIX	(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
	Hardware
834A	
	Body clips, black (12) (standard size)
347	Nuts, 4mm flanged ny lon locking, serrated (black) (10)
985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)
229	Screws, 2.5x10mm cap-head machine (hex drive) (6)
236	Screws, 2.5x12mm cap-head machine (6)
215	Screws, 2.5x6mm cap-head machine (hex drive) (6)
2577	Screws, 3x10mm button-head machine (hex drive) (6)
2587	Screws, 3x10mm cap-head machine (6) (no washer)
2551	Screws, 3x10mm countersunk machine (6) (hex drive)
859	Screws, 3x10mm flat-head machine (hex drive)(4)
2578	Screws, 3x12mm button-head machine (hex drive)(6)
2552	Screws, 3x12mm countersunk machine (6) (hex drive)
2593	Screws, 3x14mm button-head machine (hex drive)(6)
2579	Screws, 3x15mm button-head machine (hex drive)(6)
2553	Screws, 3x15mm countersunk machine (6) (hex drive)
356	Wheel hubs, hex (disc brake rotors) (4)
	LED Lights
385	LED light harness/ power harness/ zip ties (9)/ mounts (2) (fits #9333
	or 9335 body)
	Motors & Electronics
260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input
200	voltage)
072A	Gear set (for 2070, 2075 servos)
272	Gear set (for 2270 waterproof servo)
785	Motor, Titan® 12T (12-Turn, 550 size)
390	Plate, motor
271	Servo case/ gaskets (for 2270 waterproof servo)
2074	Serv o case/gaskets (for 2056 and 2075 waterproof serv os)
345	Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1))
345G	Servo saver nuts, aluminum, green-anodized (hex (1), servated (1))
345R	 (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1))
344	Servo saver / servo saver spring/ servo horn, steering
075R	Servo, digital high-speed, metal gear (ball bearing), waterproof
2075	Servo, digital high-torque (ball bearing), waterproof
075X	Servo, digital high-torque, metal gear (ball bearing), waterproof
270	Servo, digital high-torque, metal gear (ball bearing), waterproof
350R	Velineon® VXL-3s Brushless Power System, waterproof
	(includes VXL-3s waterproof ESC, Velineon 3500 motor, and
	speed control mounting plate (part #3725R))
355R	Velineon® VXL-3s Electronic Speed Control, waterproof
	(brushless) (fwd/rev/brake)
018R	XL-5 Electronic Speed Control, waterproof (land version, low-voltage
	detection, fwd/rev/brake)

Page 2 Factory Five '35 Hot Rod Truck: TQ[™] 2.4GHz Radio (Model 93034-4) Parts List

	Radio System, Batteries & Chargers	6511 3018R	Traxxas Link™ Wireless Module XL-5 Electronic Speed Control, waterproof (land version, low-voltage
2842X	5000mAh 7.4v 2-Cell 25C LiPo iD® Battery	30101	detection, fwd/rev/brake)
2843X	5800mAh 7.4v 2-Cell 25C LiPo iD® Battery		Ready-To-Race Model
2869X	7600mAh 7.4v 2-Cell 25C LiPo iD® Battery	93034-4	Factory Five '35 Hot Rod Truck: 1/10 Scale AWD Truck with TQ™
2976 2938X	AC to DC converter, 40W Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries	93034-4	2.4GHz radio system
29307	to separate balance ports)		Rear Suspension
2943	Battery charge indicators (green (4), blue (4), gray (4))	0000	=
6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	8329 8352	Bulkhead, rear
	6530 transmitters)	8334	Carriers, stub axle (left & right) Mounts, suspension arms (front & rear)/ hinge pin retainers (4)
2914	Battery, Power Cell AA Alkaline (4)	8334X	Mounts, suspension arms, aluminum (blue-anodized) (front &
2923X	Battery, Power Cell iD®, 3000mAh (NiMH, 7-C flat, 8.4V)	0004/	rear)/ hinge pin retainers (12)/ inserts (6)
2940X	Battery, Series 3 Power Cell iD®, 3300mAh (NiMH, 7-C flat, 8.4V)	8334G	Mounts, suspension arms, aluminum (green-anodized) (front &
2950X 2960X	Battery, Series 4 Power Cell iD®, 4200mAh (NiMH, 7-C flat, 8.4V) Battery, Series 5 Power Cell iD®, 5000mAh (NiMH, 7-C flat, 8.4V)		rear)/ hinge pin retainers (12)/ inserts (6)
2980	Battery/charger completer pack (includes #2969 2-amp NiMH	8334R	Mounts, suspension arms, aluminum (red-anodized) (front &
2000	peak detecting AC charger (1), #2923X 3000mAh 8.4V 7-cell NiMH	1985	rear)/ hinge pin retainers (12)/ inserts (6)
	iD® battery (1))	2754	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings) Stub axle pins (4)
2992	Battery/charger completer pack (includes #2970 iD® charger (1),	8354	Stub axles (front or rear) (2)
	#2843X 5800mAh 7.4V 2-cell 25C LiPo iD® battery (1))	9331	Suspension arms, rear (2)
2260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input	8340	Suspension pin set, complete (front & rear)
2969	voltage) Charger, AC, 2 amp NiMH peak detecting (5-7 cell, 6.0-8.4 volt, NiMH	8341X	Turnbuckles, aluminum (blue-anodized), camber links, 32mm
2000	only)		(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/
2975	Charger, DC, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH)		aluminum wrench
2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery	8341G	Turnbuckles, aluminum (green-anodized), camber links, 32mm
	Identification		(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto	8341R	Turnbuckles, aluminum (red-anodized), camber links, 32mm
0074	Battery Identification	~~ * * * * *	(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification		aluminum wrench
2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto		Shock Oil
	Battery Identification	5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto	5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
	Battery Identification	5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
6525	Communication link, telemetry expander	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
6512	Cover plate, Traxxas Link™ Wireless Module	5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
2978	Fuse, charger, 5A (2) (for #2974, 2975, 2977)	5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
2072A	Gear set (for 2070, 2075 serv os)	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
2272 2968X	Gear set (for 2270 waterproof servo)	5029	Shock oil bottle (60cc) (for mixing shock oil)
23007	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for	5038	80 wt premium shock oils with spinning carousel rack)
	Traxxas® iD® batteries)	5036	Spinning carousel rack
6560	Mount, telemetry expander (fits 4-Tec® 2.0 & 3.0)		Shocks (GTR)
6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal	7065	Caps and spring retainers, GTR shock (upper cap (2)/ hollow balls
	pad		(4)/ bottom cap (2)/ upper retainer (2)/ lower retainer (2))
6510	Popoliy or migro TO 2 (GHz (2 channel)	7029	
6519	Receiver, micro, TQ 2.4GHz (3-channel)	7028	Hollow balls (20)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	7028X	Hollow balls (20) Hollow balls, steel (machined)
	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone	7028X 7067	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	7028X	Hollow balls (20) Hollow balls, steel (machined)
6533 6552	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease)	7028X 7067	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons,
6533 6552 6526	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature	7028X 7067 7062 6961 6961T	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TiN-coated (2)
6533 6552 6526 6527 6521 2271	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo)	7028X 7067 7062 6961	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2)
6533 6552 6526 6527 6521 2271 2074	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Serv o case/gaskets (for 2056 and 2075 waterproof servos)	7028X 7067 7062 6961 6961T	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TiN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2)
6533 6552 6526 6527 6521 2271 2074 8345	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1))	7028X 7067 7062 6961 6961T	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TiN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) SUTTIES
6533 6552 6526 6527 6521 2271 2074	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated	7028X 7067 7062 6961 6961T 9360	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, tiN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs, shock (red) (1.029 rate) (2)
6533 6552 6526 6527 6521 2271 2074 8345 8345G	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof serv os) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1))	7028X 7067 7062 6961 6961T 9360 9361	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spuir Gears & Pinion Gears
6533 6552 6526 6527 6521 2271 2074 8345	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated	7028X 7067 7062 6961 6961T 9360 9361 2728	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) <u>Springs</u> Springs, shock (red) (1.029 rate) (2) <u>Splur Gears & Pinion Gears</u> Ball bearings (5x8x2.5mm) (2)
6533 6552 6526 6527 6521 2271 2074 8345 8345G 8345G	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1))	7028X 7067 7062 6961 6961T 9360 9361 2728 8323	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Splir Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345G 8345R 8344	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver / serv o saver spring/ serv o horn, steering	7028X 7067 7062 69611 9360 9361 2728 8323 1918	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR composite, front or rear (assembled, without springs) (2) Shorks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spliff Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345 8345 8344 2075 2075 2075 X	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof	7028X 7067 7062 6961 6961T 9360 9361 2728 8323	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Splir Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345 8345 8344 2075 2075 2075 2075 X 2270	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, day er / servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	7028X 7067 7062 6961 6961T 9360 9361 2728 8323 1918 2419	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) <u>Springs</u> Springs, shock (red) (1.029 rate) (2) <u>Spliff Gears & Pinion Gears</u> Ball bearings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 19-T pinion (48-pitch) / set screw
6533 6552 6526 6527 6521 2271 2074 8345 8345G 8345G 8345R 8344 2075R 2075 2075X 2075X 2075X	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2256 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, tiN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Sintings Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Source (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw
6533 6552 6526 6527 6521 2271 2274 8345 8345 8345 8345 8344 2075 2075 2075 2075 X 2270	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2056 and 2075 waterproof serv os) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver / serv o saver spring/ serv o horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, riN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Short, GTR shock, red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw
6533 6552 6526 6527 6521 2074 8345 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver / servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, gear digital bear bear gear (ball bear bear gear gear digital bear bear gear gear (ball bear bear gear	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spliff Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw
6533 6552 6526 6527 6521 2271 2074 8345 8345G 8345G 8345R 8344 2075R 2075 2075X 2075X 2075X	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with	7028X 7067 7062 6961 9360 9361 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs (5x82.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) / set screw
6533 6552 6526 6527 6521 2074 8345 8345 8345 8345 2075 2075 2075 2075 2075 2075 2075 207	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver / servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, gear digital bear bear gear (ball bear bear gear gear digital bear bear gear gear (ball bear bear gear	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, riN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Sintings Springs, shock (red) (1.029 rate) (2) Sintings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (25-tooth) (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) (fits 3mm shaft)/ set screw
6533 6552 6526 6527 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2424 2426 4725 4728 8359	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, riN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Surfings Springs, shock (red) (1.029 rate) (2) Splift Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) / set screw Gear, pinion (28-tooth) (48-pitch) (fits 3mm shaft)/ set screw
6533 6552 6526 6527 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver ruts, aluminum, red-anodized (hex (1), serrated (1)) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link TM enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas	7028X 7067 7062 6961 9360 9361 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TIN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 62-tooth Spur gear, 70-tooth
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345 8344 2075 2075X 2270 6553X 6550X 6551X 6559R	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver / servo sav er spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2424 2426 4725 4728 8359	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TIN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs, shock (red) (1.029 rate) (2) Springs (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (28-tooth) (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 72-tooth (48 pitch)
6533 6552 6526 6527 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, tiN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Spirings Springs, shock (red) (1.029 rate) (2) Spirings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 62-tooth Spur gear, 72-tooth (48 pitch) Steering Components
6533 6552 6526 6527 2271 2074 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link TM enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link TM Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQ 2.4GHz, 2-channel (transmitter only)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, riN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Surfings Springs, shock (red) (1.029 rate) (2) Splift Gears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-Tototh (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 72-tooth (48 pitch) SteerFILG Components Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1))
6533 6552 6526 6527 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver ruts, aluminum, red-anodized (hex (1), serrated (1)) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry expander 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link TM Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Z.4GHz, 2-channel (tra	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368 8345 8345 8345 8345	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ trav el limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, TIN-coated (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs, shock (red) (1.029 rate) (2) Ball bearings (5x8x2.5mm) (2) Gear cov er (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 19-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, pinion (25-tooth) (48-pitch) / set screw Gear, pinion (25-tooth) (48-pitch) fits 3mm shaft)/ set screw Gear, pinion (28-tooth) (48-pitch) fits 3mm shaft)/ set screw Spur gear, 70-tooth Spur gear, 72-tooth (48 pitch) Steering Contingonents Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1))
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Serv o case/ gaskets (for 2056 and 2075 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo, saver ruts, aluminum, red-anodized (hex (1), serrated (1)) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi 2.4GHz, 2-channel (transmitter only)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spliff Cears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 62-tooth Spur gear, 72-tooth Spur gear, 72-tooth (48 pitch) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1))
6533 6552 6526 6527 2271 2074 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2270 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0. TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi 2.4GHz, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368 8345 8345G 8345R 8344	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spliff Cears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 70-tooth Spur gear, 72-tooth (48 pitch) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1))
6533 6552 6526 6527 6521 2271 2074 8345 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2270 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver/ servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi 2.4GHz, 2-channel (transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368 8345 8345 8345 8345 8345 8345 8345 834	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs , shock (red) (1.029 rate) (2) Springs , shock (red) (1.029 rate) (2) Springs , shock (red) (1.029 rate) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 70-tooth Spur gear, 70-tooth Spur gear, 72-tooth (48 pitch) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, hardware
6533 6552 6526 6527 6521 2271 2074 8345 8345 8344 2075 2075 2075 2075 2075 2075 2075 2075	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel) Seal kit, expander box (includes o-ring, seals, and silicone grease) Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage Sensor, temperature and voltage (long) Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2270 waterproof servos) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver servo saver spring/ servo horn, steering Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0. TQi radio system (for use only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi 2.4GHz, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)	7028X 7067 7062 6961 9360 9361 2728 8323 1918 2419 2421 2422 2423 2424 2426 4725 4728 8359 8357 8368 8345 8345G 8345R 8344	Hollow balls (20) Hollow balls, steel (machined) Piston, damper (2x0.5mm hole, red) (4)/ travel limiters (4) Rebuild kit, GTR composite shocks (x-rings, bladders, pistons, e-clips, shock rod ends, hollow balls) (renews 2 shocks) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shaft, GTR shock, steel (2) Shocks, GTR composite, front or rear (assembled, without springs) (2) Springs Springs, shock (red) (1.029 rate) (2) Spliff Cears & Pinion Gears Ball bearings (5x8x2.5mm) (2) Gear cover (rear chassis brace)/ wire retainer Gear, 18-T pinion (48-pitch) / set screw Gear, 21-T pinion (48-pitch) / set screw Gear, 22-T pinion (48-pitch) / set screw Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 24-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Gear, 72-tooth (48-pitch) (fits 3mm shaft)/ set screw Spur gear, 70-tooth Spur gear, 72-tooth (48 pitch) Servo saver nuts, aluminum, blue-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, green-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1)) Servo saver nuts, aluminum, red-anodized (hex (1), serrated (1))

	Suspension Linkage
8341	Camber link/toe link set (plastic/ non-adjustable) (front & rear)
8341X	Turnbuckles, aluminum (blue-anodized), camber links, 32mm
	(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
8341G	Turnbuckles, aluminum (green-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
8341R	Turnbuckles, aluminum (red-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/
	aluminum wrench
	Team Traxxas Items
2514 9950	Decal sheet, racing sponsors Official Team Traxxas® racing decal set (flag logo/ 6-color)
9909	Traxxas® racing banner, red & black (3x7 feet)
	Tires & Wheels
9373	Tires and wheels, assembled, glued (black with chrome wheels, 2.1"
	Response tires) (extra wide, rear) (2)
9372	Tires and wheels, assembled, glued (black with chrome wheels, 2.1"
	Response tires) (front) (2) Traxxas Tools
24228	
3433X 3433	Body reamer (aluminum handle) Body reamer (plastic handle)
3435 3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
8721	and 8.0mm), 1/4" drive Speed bit handle, medium (one piece)
8720	Speed bit handle, premium, large (rubber overmold)
8722	Speed bit handle, premium, medium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm),
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive
8715	3.0mm), 1/4" drive Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
8715X	2.5mm), 1/4" drive Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
	2.5mm, 3.0mm), 1/4" drive
2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle
	Turnbuckles & Threaded Rods
0044	
8341	Camber link/toe link set (plastic/ non-adjustable) (front & rear)
8342	Toe links, steel (34mm) (2)
8341X	Turnbuckles, aluminum (blue-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ too links, 34mm (2)/
	(front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/ aluminum wrench
8341G	Turnbuckles, aluminum (green-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/
8341R	aluminum wrench Turnbuckles, aluminum (red-anodized), camber links, 32mm (front) (2)/ camber links, 28mm (rear) (2)/ toe links, 34mm (2)/

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com TRAXXAS.COM