

Sledge® (Model 95076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	9639R	Shock tower, front, 7075-T6 aluminum (red-anodized) (fits
4889X	Ball bearings, black rubber sealed (10x19x5mm) (2)	9538	Sledge®) Shock tower, rear, 6061-T6 aluminum (blue-anodized)
5114A	Ball bearings, black rubber sealed (5x8x2.5mm) (2)	9538A	Shock tower, rear, 6061-T6 aluminum (gray-anodized)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)	9538G	Shock tower, rear, 6061-T6 aluminum (green-anodized)
5118A	Ball bearings, black rubber sealed (8x16x5mm) (2)	9538T	Shock tower, rear, 6061-T6 aluminum (orange-anodized)
5105	Ball bearings, blue rubber sealed (6x10x3mm) (2)	9538R	Shock tower, rear, 6061-T6 aluminum (red-anodized)
	Body & Accessories	9638	Shock tower, rear, 7075-T6 aluminum (blue-anodized) (fits Sledge®)
1926 1726	Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	9638A	Shock tower, rear, 7075-T6 aluminum (dark titanium-anodized)
9510 9510X	Body reinforcement set, black/ skid pads (roof) (fits #9511 body)	9638G	(fits Sledge®) Shock tower, rear, 7075-T6 aluminum (green-anodized) (fits
9510A 9510G	Body reinforcement set, blue/ skid pads (roof) (fits #9511 body) Body reinforcement set, green/ skid pads (roof) (fits #9511 body)		Sledge®)
9510T	Body reinforcement set, green said pads (roof) (fits #9511 body) body)	9638T	Shock tower, rear, 7075-T6 aluminum (orange-anodized) (fits Sledge®)
9510R	Body reinforcement set, red/ skid pads (roof) (fits #9511 body)	9638R	Shock tower, rear, 7075-T6 aluminum (red-anodized) (fits Sledge®)
9513X	Body support (assembled with front mount & rear latch)/ skid pads (roof) (left & right)	9524	Side guards, chassis (left and right)/ 3x8 CCS (10)
9513	Body support, center/ 3x12 CS (8) (fits Sledge®)	9527	Tie bars, front, 6061-T6 aluminum (blue-anodized)
9511	Body, Sledge® (clear, requires painting)/window, grille, lights	9527A	Tie bars, front, 6061-T6 aluminum (dark titanium-anodized)
	decal sheet	9527G 9527T	Tie bars, front, 6061-T6 aluminum (green-anodized) Tie bars, front, 6061-T6 aluminum (orange-anodized)
9511A	Body, Sledge®, blue (painted, decals applied) (assembled with front	9527T	Tie bars, front, 6061-T6 aluminum (red-anodized)
	& rear body mounts and rear body support for clipless mounting)	9629	Tie bars, front, 7075-T6 aluminum (led-anodized) (fits Sledge®)
9511G	Body, Sledge®, green (painted, decals applied) (assembled with front & rear body mounts and rear body support for clipless mounting)	9629A	Tie bars, front, 7075-T6 aluminum (dark titanium-anodized) (fits
9511T	Body, Sledge®, orange (painted, decals applied) (assembled with	9629G	Sledge®) Tie bars, front, 7075-T6 aluminum (green-anodized) (fits
9511X	front & rear body mounts and rear body support for clipless mounting) Body, Sledge®, ProGraphix® (graphics are printed, requires		Sledge®)
9511R	paint & final color application)/ window, grille, lights decal sheet Body, Sledge®, red (painted, decals applied) (assembled with front &	9629T	Tie bars, front, 7075-T6 aluminum (orange-anodized) (fits Sledge®)
331110	rear body mounts and rear body support for clipless mounting)	9629R	Tie bars, front, 7075-T6 aluminum (red-anodized) (fits Sledge®)
2514	Decal sheet, racing sponsors	9528 0528 A	Tie bars, rear, 6061-T6 aluminum (blue-anodized)
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)	9528A 9528G	Tie bars, rear, 6061-T6 aluminum (dark titanium-anodized) Tie bars, rear, 6061-T6 aluminum (green-anodized)
	Bumpers & Skidplates	9528T	Tie bars, rear, 6061-T6 aluminum (green-anodized)
9535	Bumper, front/ skidplate, front/ tie bar mount, front/ 3x25 CS (2)	9528R	Tie bars, rear, 6061-T6 aluminum (crange-anodized)
9536	Bumper, rear/ skidplate, rear/ tie bar mount, rear/ 3x25 CS (2)	9630	Tie bars, rear, 7075-T6 aluminum (blue-anodized) (fits Sledge®)
	Chassis & Attachments	9630A	Tie bars, rear, 7075-T6 aluminum (dark titanium-anodized) (fits
9514	Body mount, front		Sledge®)
9515	Body mount, front Body mount, rear/ shock guard (body retainer), front	9630G	Tie bars, rear, 7075-T6 aluminum (green-anodized) (fits Sledge®)
9624	Box, receiver (sealed) w/ ESC mount/ receiver box cover/ access	9630T	Tie bars, rear, 7075-T6 aluminum (orange-anodized) (fits Sledge®)
	plug/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x10 BCS (4)	9630R	Tie bars, rear, 7075-T6 aluminum (red-anodized) (fits Sledge®)
9523	Center brace (T-Bar), 6061-T6 aluminum (black-anodized)/ 3x16 SS (2)	7799	Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels)
9523G	Center brace (T-Bar), 6061-T6 aluminum (green-anodized)/ 3x16	9626 9576	Tray, battery
	SS (2)	9576X	Wheelie bar, black (assembled)/ 3x20 CS (8) Wheelie bar, blue (assembled)/ 3x20 CS (8)
9523T	Center brace (T-Bar), 6061-T6 aluminum (orange-anodized)/ 3x16	9576G	Wheelie bar, green (assembled)/ 3x20 CS (8)
05001	SS (2)	9576T	Wheelie bar, orange (assembled)/ 3x20 CS (8)
9523X	Chassis brace (T-Bar), 6061-T6 aluminum (blue-anodized)/ 3x16 SS (2)	9576R	Wheelie bar, red (assembled)/ 3x20 CS (8)
9523A	Chassis brace (T-Bar), 6061-T6 aluminum (dark titanium-	7775X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ axle,
0====	anodized)/ 3x16 SS (2) (fits Sledge®)	7775A	wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4) Wheels, wheelie bar, 6061-T6 aluminum (dark titanium-anodized)
9523R	Chassis brace (T-Bar), 6061-T6 aluminum (red-anodized)/ 3x16 SS (2)	11134	(2)/ axle, wheelie bar, 6061-16 aluminum (2)/ 10x15x4 ball bearings (4)
9520	Chassis brace, front/ 4x15 CCS (2)	7775G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
9521	Chassis braces (rear (1), rear tower (2))/ 4x15 CCS (4)		axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
9522 9522G	Chassis, aluminum (blue-anodized)		(4)
9522G 9522R	Chassis, Sledge®, aluminum (green-anodized) Chassis, Sledge®, aluminum (red-anodized)	7775T	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/
9522A	Chassis, Sledge®, aluminum (red-anodized)		axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings
9627	Hold down, battery	777FD	(4)
9516	Latch, body mount, rear	7775R	Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)
9628	Retainer, battery hold-down (front and rear) (1 each)	9518	Wing mount
9625	Seal kit, receiver box (includes o-ring, seals, and silicone grease)	9512	Wing washer (1)
9539	Shock tower, front, 6061-T6 aluminum (blue-anodized)	9617	Wing washer, 6061-T6 aluminum (blue-anodized) (1)/ 4x12mm
9539A	Shock tower, front, 6061-T6 aluminum (gray-anodized)		FCS (2)
9539G	Shock tower, front, 6061-T6 aluminum (green-anodized)	9617A	Wing washer, 6061-T6 aluminum (dark-titanium anodized) (1)/
9539T	Shock tower, front, 6061-T6 aluminum (orange-anodized)		4x12mm FCS (2)
9539R 9639	Shock tower, front, 6061-T6 aluminum (red-anodized) Shock tower, front, 7075-T6 aluminum (blue-anodized) (fits	9617G	Wing washer, 6061-T6 aluminum (green-anodized) (1)/ 4x12mm FCS (2)
9639A	Sledge®) Shock tower, front, 7075-T6 aluminum (dark titanium-anodized)	9617T	Wing washer, 6061-T6 aluminum (orange-anodized) (1)/ 4x12mm FCS (2)
0000A	(fits Sledge®)	9617R	Wing washer, 6061-T6 aluminum (red-anodized) (1)/ 4x12mm
9639G	Shock tower, front, 7075-T6 aluminum (green-anodized) (fits Sledge®)	9517X	FCS (2) Wing/ wing washer (blue)/ 4x12mm FCS (2)
9639T	Shock tower, front, 7075-T6 aluminum (orange-anodized) (fits	9517G	Wing/ wing washer (green)/ 4x12mm FCS (2)
	Sledge®)	9517T	Wing/ wing washer (orange)/ 4x12mm FCS (2)

Page 2 Sledge	e®: TQi Traxxas	Link Enabled	2.4GHz Radio 8	& TSM ((Model 95076-4)	Parts List
---------------	-----------------	--------------	----------------	---------	-----------------	------------

9517A Wir 9517 Wir 9517 Wir 9517 Wir 9581X Car 9581A Car 9581G Car 9581R Car 9581R Car 9581 Car 9581 Car 9583 Diff 9583 Diff 9583 Diff 9586 Diff 9586 Diff 9587 Driv Sle 9587 Driv 9587 Gas 9581 Moo 9584 Moo 9585 Diff 9587 Car 9587 Car 9587 Coil, 9587 Coil, 9587 Coil, 9579 Rin 9579 Rin 9579 Soo 9552 Car 9552 Car 9552 Car 9552 Car 9552 Car 9552 Car	/ing/ wing washer (red)/ 4x12mm FCS (2) /ing/ wing washer (white)/ 4x12mm FCS (2) /ing/ wing washer/ 4x12mm FCS (2)	9680 9551 9656X 9553 9554 9553X 9554X 8654G 8654G 8654A 7758A 7758G 7758T 7758R 9547 9547A	O-rings (6) Rebuild kit, steel constant-velocity driveshaft (includes pins for 2 driveshaft assemblies) (for #9550 front or #9654X rear steel CV driveshafts) Rebuild kit, steel constant-velocity driveshafts, center (front or rear) (includes pins for 2 driveshaft assemblies) (for #9655X steel CV driveshafts) Stub axle, front Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
9517 Wir 4889X Ball 9581X Car bus 9581A Car 9581G Car bus 9581F Car bus 9581 Car 9581 Car 9581 Car 9581 Car 9581 Car 9583 Diff 9583 Diff 9586 Diff 9586 Diff 9586 Diff 9587 Driv 679587 Driv 9587 Gea 9587 Moriv 9584 Moriv 9585 Car 9585 Car 9552 Car 9552 Car 9552 Car 9552 Car 9552 Car 9552 Car 9552 Car	Initial Common (Initial Common	9656X 9553 9554 9553X 9554X 8654 8654G 8654A 8654R 7758A 7758G 7758T 7758R	driveshaft assemblies) (for #9550 front or #9654X rear steel CV driveshafts) Rebuild kit, steel constant-velocity driveshafts, center (front or rear) (includes pins for 2 driveshaft assemblies) (for #9655X steel CV driveshafts) Stub axle, front Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
4889X Ball 9581X Car bus 9581A Car 9581G Car 9581G Car 9581T Car 9581R Car 9581 Car 9581 Car 9581 Car 9581 Car 9581 Car 9581 Car 9588 Diff 9583 Diff 9583 Diff 9586 Diff 9587 Driv 9587 Driv 9587 Driv 9582 Gea 9584 Moo 9584A Moo and 9584A Moo	all bearings, black rubber sealed (10x19x5mm) (2) arrier, differential (aluminum, blue-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, dark titanium-anodized)/ ifferential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) ifferential, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9553 9554 9553X 9554X 86544 8654G 8654A 8654A 7758A 7758G 7758T 7758R 9547	driveshafts) Rebuild kit, steel constant-velocity driveshafts, center (front or rear) (includes pins for 2 driveshaft assemblies) (for #9655X steel CV driveshafts) Stub axle, front Stub axle, front Stub axles, nardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
9581X Car bus 9581A Car diff 9581G Car bus 9581R Car bus 9581R Car bus 9581R Car gas 8680 Diff 5136X Diff 5136X Diff 5136X Diff 9583 Diff 9586 Diff 9587 Driv driv 9587 Driv driv 9582 Geat 9584 Mot and 9584A Mot and 9584A	all bearings, black rubber sealed (10x19x5mm) (2) arrier, differential (aluminum, blue-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, dark titanium-anodized)/ ifferential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) ifferential, front or rear (hardened steel) (for differential pinion gear)/ ive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ iveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) iount, center differential carrier, 6061-T6 aluminum (blue- lount, center differential carrier, 6061-T6 aluminum (dark	9553 9554 9553X 9554X 86544 8654G 8654A 8654A 7758A 7758G 7758T 7758R 9547	Rebuild kit, steel constant-velocity driveshafts, center (front or rear) (includes pins for 2 driveshaft assemblies) (for #9655X steel CV driveshafts) Stub axle, front Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581X Car bus 9581A Car diff 9581G Car bus 9581G Car bus 9581R Car bus 9581R Car gas 8680 Diff 5136X Diff 5136X Diff 9588 Diff 9588 Diff 9588 Diff 9588 Diff 9588 Diff 9588 Diff 9580 Diff 9580 Diff 9581 Car car div 9582 Gas car div 9584 Moo and 9584 Moo and 9584A Moo and 9584A Moo and 9584B Moo and 9584B Moo and 9584B Moo and 9584C Gar dig 9552 Car ges 9552 Car ges 9552 Car righ 9552 Car ges	arrier, differential (aluminum, blue-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, dark titanium-anodized)/ differential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTEE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9554 9553X 9554X 8654 8654G 8654A 8654R 7758A 7758A 7758G 7758T 7758R	steel CV driveshafts) Stub axle, front Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581A Car diff 9581G Car bus 9581T Car bus 9581R Car gas 8680 Diff 5136X Diff 9586 Diff 9586 Diff 9586X Diff 9587 Driv driv 9587 Driv Sle 9587 Driv driv 9584 Moo and 9584A Moo and 9584	ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, dark titanium-anodized)/ ifferential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9554 9553X 9554X 8654 8654G 8654A 8654R 7758A 7758A 7758G 7758T 7758R	Stub axle, front Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
9581A Car diff 9581G Car bus 9581T Car bus 9581R Car bus 9581R Car 9581 Car 9581 Car 9581 Car 9582 Diff 9587 Diff 9587 Driv driv 9584 Moo 9	arrier, differential (aluminum, dark titanium-anodized)/ ifferential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9554 9553X 9554X 8654 8654G 8654A 8654R 7758A 7758A 7758G 7758T 7758R	Stub axle, rear (for use only with #9557 rear driveshaft) Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
Section	ifferential bushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) (ount, center differential carrier, 6061-T6 aluminum (blue-nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9553X 9554X 8654A 8654G 8654A 7758A 7758G 7758T 7758R 9547	Stub axles, hardened steel (2) (for steel constant-velocity driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581G Car bus 9581T Car bus 9581R Car gas 8680 Diff 12 5136X Diff 5136X Diff 9588 Diff 9586X Diff 9587 Driv 3587 Driv 3584 Moo 9584 Moo	arrier, differential (aluminum, green-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ orings (2)/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, center, complete (fits Sledge®) ifferential, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear ants (2)/ spacers (4)) ount, center differential carrier, 6061-T6 aluminum (blue-lount, center differential carrier, 6061-T6 aluminum (dark	9554X 8654G 8654A 8654A 7758A 7758G 7758T 7758R 9547	driveshafts) (fits Sledge®) Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mn pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581T bus 9581R Car bus 9581R Car 9581R Car 9581 Car 9581 Car 9581 Car 9583 Diff 9586 Diff 9586 Diff 9587 Driv driv 9582 Gea 9584 Moo 9584A Moo 9584A Moo 9584A Moo and 9584B Moo 9584B Mo	arrier, differential (aluminum, orange-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential differential bushing (metal)/ o-rings (2)/ ring gear asket arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear anafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue-nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654A 8654A 8654A 7758A 7758G 7758T 7758R 9547	Stub axles, hardened steel (2) (for use only with #9557 driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mn pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
Section	ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket differential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654G 8654A 8654R 7758A 7758G 7758T 7758R 9547	driveshaft) (fits Sledge®) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mn pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581R Car bus 9581 Car sus 8680 Diff 12.2 5136X Diff 5136X Diff 5136X Diff 95883 Diff 9586X Diff 9586X Diff 95887 Driv Griv 9587 Driv Griv 9582 Gee sha 9584A Moo 9584A Moo 9584A Moo 9584A Moo 9584A Moo and 9584B Moo and 9584B Moo and 9584C Oil, 5135 Oil, 5137 Oil, 5579R Rin 9579R Rin 9579R Rin 9579R Car 19552A Car 19552C Car 19552C Car	arrier, differential (aluminum, red-anodized)/ differential ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket differential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear anafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654G 8654A 8654R 7758A 7758G 7758T 7758R 9547	pin (4) Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Front \$\subseteq \text{SUSIGISTO}\$ Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581 Carr gas 8680 Diffs 12.2 5136X Diffs 5136X Diffs 5136X Diffs 95883 Diffs 95885 Diffs 95880 Diffs 9587X Driv 9582 Gea 9584 Moor 9584A Moor 9584A Moor 9584A Moor 9584A Moor 9584B Moor	ushing/ ring gear gasket/ 3x10mm CCS (4) arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear aafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654A 8654R 7758A 7758G 7758T 7758R 9547	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) FIGURES SISTER Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9581 Car gas 8680 Diffs 12.2 5136X Diffs 5136X Diffs 5136X Diffs 9586 Diffs 9586 Diffs 9586 Diffs 9587 Driv driv 9587 Driv driv 9582 Ges sha 9584 Moo 9584X Moo and 9584R Moo 9584R Moo and 9584R Moo	arrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (bluenodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654A 8654R 7758A 7758G 7758T 7758R 9547	3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From Sisian (1) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9388880 Diffi 12.3 5136X Diffi 5136X Diffi 5136X Diffi 95883 Diffi 95886 Diffi 95886 Diffi 95885 Diffi 95887 Driv 9587 Driv 9582 Gea 9584 Moo and 95844 Moo and 95844 Moo and 95845 Moo and 95846 Moo and 95847 Div 95847 Moo and 95848 Moo and	asket ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654R 7758A 7758 7758G 7758T 7758R 9547	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
8680 Diff 12.3 5136X Diff 5136X Diff 5136X Diff 5136X Diff 9588 Diff 9588 Diff 9588 Diff 9588 Diff 9587 Driv Sle 9587 Driv 9582 Gea 9584 Moo and 9584A Moo a	ifferential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 2.2x18x0.5 PTFE-coated washer (1) ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear lafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	8654R 7758A 7758 7758G 7758T 7758R 9547	(4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
5136X Diff 5136X Diff 9583 Diff 9586 Diff 9586X Diff 9586X Diff 9585 Diff 9580 Diff 9587 Driv 9582 Gea 9584 Mod 9584X Mod 9584A Mod 9584A Mod 9584A Mod 9584B Mod 9584G	ifferential oil kit (1 each: 10K, 30K, 50K weights) ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- lount, center differential carrier, 6061-T6 aluminum (dark	7758A 7758 7758G 7758T 7758R 9547	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Front \$\subseteq \text{IS G S O } Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
5136X Diff 9583 Diff 9586 Diff 9586X Diff 9585 Diff 9580 Diff 9587 Driv driv Sle 9582 Ges sha 9584 9584 Moo 9584A Moo 9584B Moo 9584G Oil, 5130 Oil, 5135 Oil, 5137 Oil, 9579 Rin 9579 Rin 9552 Car 9552X	ifferential oil kit (1.7 oz (50cc) of 1 each: 10K, 30K, 50K weights) ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (bluelount, center differential carrier, 6061-T6 aluminum (dark	7758 7758G 7758T 7758R 9547 9547X	Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From Sisia (1) Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9583 Diff 9586 Diff 9586 Diff 9586X Diff 9585 Diff 9587 Driv 9587 Driv 9582 Gea 9584 Moo 9584X Moo and 9584A Moo 9584A Moo 9584B Moo 958	ifferential output cup, front or rear (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear hafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (bluenodized) lount, center differential carrier, 6061-T6 aluminum (dark	7758 7758G 7758T 7758R 9547 9547X	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From SISISION Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9586 Diffi 9586X Diffi 9586X Diffi 9586X Diffi 9580 Diffi 9580 Diffi 9587 Driv 9587 Driv 9582 Gea 9584 Moo 9584X Moo and 9584A Moo and and 9584A Moo and 9584A Moo and and 9584A Moo and 9584A Moo and 9584A Moo and and 9584A Moo	ifferential output cup, center (hardened steel)/ 2.5x12mm pin ifferential output cup, center (hardened steel, heavy duty) (2)/ 5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue-nodized) lount, center differential carrier, 6061-T6 aluminum (dark	7758G 7758T 7758R 9547 9547X	Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From SISIBISION Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9586X Diff 2.5; 9585 Diff 9580 Diff 9587X Driv 9587X Driv 9582 Gea 9584 Moo and 9584X Moo and 9584A	ifferential output cup, center (hardened steel, heavy duty) (2)/5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	7758T 7758R 9547 9547X	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From SISICID Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
2.52 9585 Diff 9587 Diff 9587X Driv 9587 Sle 9587 Driv driv 9582 Gee sha 9584X Moo 9584A Moo 9584A Moo 9584B Moo 958	5x12mm pin (2) ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547 9547X	Wheel nuts, splined, 17mm, serrated (red-anodized) (4) From \$\sigma \text{IS} I
9585 Diff 9580 Diff 9580 Diff 9587 Driv Sle 9587 Driv 9582 Gea 9584 Moo 9584X Moo 9584A Moo 9584A Moo 9584A Moo 9584A Moo 9584B Moo 9584	ifferential, center, complete (fits Sledge®) ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547 9547X	Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9580 Diff 9587X Driv Sle 9587 Driv 9582 Gee sha 9584 Moo 9584X Moo 1010 9584G Moo 1010 9584G Moo 1010 9584G Moo 1010 1010 1010 1010 1010 1010 1010 1	ifferential, front or rear, complete (fits Sledge®) rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547X	Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9587X Driv Sle 9587 Driv driv 9582 Ges Sha 9584 Mou 9584X Mou sha 9584A Mou sha 9584G Sha 9584G Car 9584G Car 9585C Car 9585C Car 9585C Car 19955C Car	rive cup, center, front or rear (steel constant-velocity) (1) (fits ledge®) rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547X	Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9587 Driv driv 9582 Gea 9584 Moo 9584X Moo 9584A Moo 9584G Moo 9584T Moo 9584T Moo 9584T Moo 9584G Oil, 5135 Oil, 5136 Oil, 5137 Oil, 9579R Rin 9579R Rin 9579R Rin 9579R Car 19552 Car 9552X Car 19552G Ca	rive cup, front or rear (hardened steel) (for differential pinion gear)/ riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark		aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9582 Ges sha 9584 Moo 9584X Moo 9584X Moo 9584A Moo sha sha 9584G Moo sha sha 9584G Moo sha	riveshaft boots (2)/ boot retainers (2) ear set, differential (output gears (2)/ spider gears (4)/ spider gear lafts (2)/ spacers (4)) lount, center differential lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547A	assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9582 Gea sha 9584 Mot 9584X Mot 9584A Mot 1tita 9584G Mot and 9584R Mot	ear set, differential (output gears (2)/ spider gears (4)/ spider gear nafts (2)/ spacers (4)) lount, center differential lount, center differential carrier, 6061-T6 aluminum (bluenodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547A	(1) Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9584 Moto 9584X Moto and 9584A Moto	nafts (2)/ spacers (4)) lount, center differential lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	9547A	Camber links, front, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9584 Mode and and 9584A Mode and 9584G Mode and 9584G Mode and 9584R Mode and 958	lount, center differential lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark	004774	7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9584X Modand 9584A Modulativa 9584G Modand 9584G Modand 9584T Modand 9584R Modand 9584R Modand 5130 Oil, 5135 Oil, 5040 Oil, 5136 Oil, 5137 Oil, 9579R Ring 9579R Ring 9559 Bod 9552 Car 9552X Car righ 9552A Car righ	lount, center differential carrier, 6061-T6 aluminum (blue- nodized) lount, center differential carrier, 6061-T6 aluminum (dark		
9584A Mod tita 9584G Mod and 9584G Mod and 9584T Mod and 9584R Mod and 5130 Oil, 5135 Oil, 5040 Oil, 5136 Oil, 5137 Oil, 9579 Ring 9579R Ring 9579R Ring 9552 Car 9552 Car 19552X Car 19552A Car 19552G Car	nodized) lount, center differential carrier, 6061-T6 aluminum (dark		ends, assembled with steel hollow balls (4)/ aluminum wrench,
9584A Montita 9584G Monand 9584T Monand 9584R Monand 5130 Oil, 5135 Oil, 5135 Oil, 5136 Oil, 5137 Oil, 5137 Oil, 9579 Rinn 9579R Rinn or r 9559 Boo 9552 Car 9552X Car righ 9552A Car righ	ount, center differential carrier, 6061-T6 aluminum (dark		8mm (1)
9584G Modano 9584T Modano 9584R Modano 9584R Modano 9584R Modano 9584R Modano 9584R Modano 95130 Oil, 5135 Oil, 5135 Oil, 5136 Oil, 5137 Oil, 9579 Rin 9579 Rin 9579R Car righ 9552 Car 9552X Car 9552X Car righ 9552G Car	tanium-anodized)	9547G	Camber links, front, Sledge® (TUBES green-anodized, 7075-T6
9584T Morano 9584R Morano 9584R Morano 5130 Oil, 5135 Oil, 5040 Oil, 5137 Oil, 9579R Ring 9579R Ring 9559 Boo 9552 Car 9552X Car righ 9552A Claf 9552G Car			aluminum, stronger than titanium) (117mm) (2)/ rod ends,
9584T Modano 9584R Modano 5130 Oil, 5135 Oil, 5040 Oil, 5137 Oil, 9579 Rinn 9579 Rinn or r 9559 Boo 9552 Car 9552X Car righ 9552A Car (Car righ	ount, center differential carrier, 6061-T6 aluminum (green-		assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)
9584R Modano 5130 Oil, 5135 Oil, 5040 Oil, 5137 Oil, 9579 Ring 9579R Ring 9579R Car 9552 Car 9552X Car righ 9552A Car righ	nodized)	9547T	Camber links, front, Sledge® (TUBES orange-anodized, 7075-T6
9584R Modand 5130 Oil, 5135 Oil, 5040 Oil, 5137 Oil, 5137 Oil, 9579 Rin 9579R Rin or r 9559 Boo 9552 Car 9552X Car righ 9552A Car (lefe 9552G Car	lount, center differential carrier, 6061-T6 aluminum (orange- nodized)		aluminum, stronger than titanium) (117mm) (2)/ rod ends,
9552A Car righ	ount, center differential carrier, 6061-T6 aluminum (red-		assembled with steel hollow balls (4)/ aluminum wrench, 8mm
5130 Oil, 5135 Oil, 5040 Oil, 5136 Oil, 5137 Oil, 9579 Rin 9579R Rin or r 9559 Boo 9552 Car 9552X Car righ 9552A Car (lef	nodized)		(1)
5040 Oil, 5136 Oil, 5137 Oil, 9579 Rin 9579R Rin or r 9559 Boo 9552 Car 9552X Car righ 9552A Clar 9552G Car	il, differential (100K wt) (0.7 oz (20cc))	9547R	Camber links, front, Sledge® (TUBES red-anodized, 7075-T6
5136 Oil, 5137 Oil, 9579 Ring 9579R Ring 9559 Boo 9552 Car 9552X Car righ 9552A Car (lef 9552G Car	il, differential (10K wt) (1.7 oz (50cc))		aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm
5137 Oil, 9579 Ring 9579R Ring 9579R Sing 9559 Boo 9552 Car 9552X Car righ 9552A Car (lefe 9552G Car	il, differential (20M wt) (standard)		(1)
9579 Ringer State	il, differential (30K wt) (1.7 oz (50cc))	9532	Caster blocks (c-hub), left & right/ kingpin bushings (4)
9579R Rin or r 9559 Boo 9552 Car 9552X Car righ 9552A Car (lef 9552G Car righ	il, differential (50K wt) (1.7 oz (50cc))	9532X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left 8
9559 Boo 9552 Car 9552X Car rigl 9552A Car (lef 9552G Car	ing gear, differential/ pinion gear, differential		right/ kingpin bushings (4)/ 3x20mm CS (with threadlock) (4)
9559 Boo 9552 Car 9552X Car righ 9552A Car (lef 9552G Car righ	ing gear, differential/ pinion gear, differential (machined) (front	9532A	Caster blocks (c-hubs), 6061-T6 aluminum (dark titanium-
9552 Car 9552X Car righ 9552A Car (lef 9552G Car righ	•		anodized), left & right/ kingpin bushings (4)/ 3x20mm CS (with threadlock) (4)
9552 Car 9552X Car righ 9552A Car (lef 9552G Car righ	Driveline Components	9532G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left
9552X Car righ 9552A Car (lef 9552G Car righ	oots, driveshaft (2)/ retainer (assembled) (2)	30020	& right/ kingpin bushings (4)/ 3x20mm CS (with threadlock) (4)
righ 9552A Car (lef 9552G Car righ	arriers, stub axle (left and right)	9532T	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),
9552A Car (lef 9552G Car righ	arriers, stub axle, 6061-T6 aluminum (blue-anodized) (left and		left & right/ kingpin bushings (4)/ 3x20mm CS (with threadlock)
9552G (lef righ	ght)/ 3x18mm CS (with threadlock) (2) arriers, stub axle, 6061-T6 aluminum (dark titanium-anodized)		(4)
9552G Car	eft and right)/ 3x18mm CS (with threadlock) (2)	9532R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &
righ	arriers, stub axle, 6061-T6 aluminum (green-anodized) (left and	9683	right/ kingpin bushings (4)/ 3x20mm CS (with threadlock) (4) Hollow balls, steel (8)
9552T Car	ght)/ 3x18mm CS (with threadlock) (2)	9632	Kingpin bushings, machined steel (4)
	arriers, stub axle, 6061-T6 aluminum (orange-anodized) (left	9598	Linkage, sway bar (front or rear)
	nd right)/ 3x18mm CS (with threadlock) (2)	9597	Mounts, sway bar/ collars (front and rear)
	arriers, stub axle, 6061-T6 aluminum (red-anodized) (left and	9539	Shock tower, front, 6061-T6 aluminum (blue-anodized)
_	ght)/ 3x18mm CS (with threadlock) (2) riveshaft, center, front (shaft only, 4mm x 88mm) (1)	9539A	Shock tower, front, 6061-T6 aluminum (gray-anodized)
	riveshaft, center, front (steel constant-velocity) (shaft only) (1)	9539G	Shock tower, front, 6061-T6 aluminum (green-anodized)
		9539T	Shock tower, front, 6061-T6 aluminum (orange-anodized)
•	or use only with #9655X steel CV driveshafts)	9539R	Shock tower, front, 6061-T6 aluminum (red-anodized)
	or use only with #9655X steel CV driveshafts) riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1)	9639	Shock tower, front, 7075-T6 aluminum (blue-anodized) (fits
•	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1)	9639A	Sledge®) Shock tower, front, 7075-T6 aluminum (dark titanium-anodized)
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts)	3033A	(fits Sledge®)
(1)	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)	9639G	Shock tower, front, 7075-T6 aluminum (green-anodized) (fits
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm))		Sledge®)
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with		Shock tower, front, 7075-T6 aluminum (orange-anodized) (fits
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with 9554 stub axle)	9639T	Sledge®)
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with e9554 stub axle) riveshaft, rear, steel constant-velocity (complete assembly) (2)		
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with 9554 stub axle)	9639T 9639R	Shock tower, front, 7075-T6 aluminum (red-anodized) (fits
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with 9554 stub axle) riveshaft, rear, steel constant-velocity (complete assembly) (2) riveshaft, rear, steel constant-velocity (shaft only) (1) (for use	9639R	Sledge®)
	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with 9554 stub axle) riveshaft, rear, steel constant-velocity (complete assembly) (2) riveshaft, rear, steel constant-velocity (shaft only) (1) (for use nly with #9654X rear steel CV driveshafts) riveshaft, steel constant-velocity (assembled), front (1) riveshafts, center, assembled (steel constant-velocity), front		Sledge®) Steering block arms (aluminum, blue-anodized) (2) (fits #9635
9632 Kin	riveshaft, center, rear (shaft only, 4mm x 146.5mm) (1) riveshaft, center, rear (steel constant-velocity) (shaft only) (1) or use only with #9655X steel CV driveshafts) riveshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)) riveshaft, rear (shaft only, 5mm x 131mm) (1) (for use only with 9554 stub axle) riveshaft, rear, steel constant-velocity (complete assembly) (2) riveshaft, rear, steel constant-velocity (shaft only) (1) (for use only with #9654X rear steel CV driveshafts) riveshaft, steel constant-velocity (assembled), front (1)	9639R	Sledge®)

Page 3 Sledge®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 95076-4) Parts Lis	Page 3	Sledge®: TQi Traxxas	Link Enabled 2.4GHz	Radio & TSM (Me	odel 95076-4) Parts List
---	--------	----------------------	---------------------	-----------------	--------------------------

•	-	•	•
9636A	Steering block arms (aluminum, dark titanium-anodized) (2) (fits #9635 series & 9637 series steering blocks)		Hardware
9636G	Steering block arms (aluminum, green-anodized) (2) (fits #9635 series & 9637 series steering blocks	1552 4859	3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1) CS 3x10 flathead (hex drive)
9636T	Steering block arms (aluminum, orange-anodized) (2) (fits #9635 series & 9637 series steering blocks)	9592X	Hardware kit, stainless steel, Sledge® (contains all hardware used on Sledge®)
9636R	Steering block arms (aluminum, red-anodized) (2) (fits #9635	9591 2584	Hardware, motor mount, Sledge®
9635X	series & 9637 series steering blocks) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right/		Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX® 2.5, 2.5R, 3.3)
	steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/ 3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm	9564 2745X	Mount, shock (steel) (2) Nuts, 3mm nylon locking, black (8)
00054	NL (2)	2744X	Nuts, 3mm nylon locking, flanged, black (8)
9635A	Steering blocks, 6061-T6 aluminum (dark titanium-anodized), left & right/ steering block arms (2)/ 4x16mm BCS (with threadlock)	1748 4858	Nuts, 4mm nylon locking, black (10) Screw, 3x25 countersunk machine (hex drive) (6)
	(4)/ 3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm NL (2)	3229 2577	Screws, 2.5x10mm cap-head machine (hex drive) (6)
9635G	Steering blocks, 6061-T6 aluminum (green-anodized), left & right/	2579	Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6)
	steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/	2586	Screws, 3x15mm cap-head machine (hex drive) (6)
	3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm	2553	Screws, 3x15mm countersunk machine (6) (hex drive)
9635T	NL (2) Steering blocks, 6061-T6 aluminum (orange-anodized), left &	2583X	Screws, 3x18mm cap-head machine (hex drive) (6)
	right/ steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/	2585	Screws, 3x20mm cap-head machine (hex drive) (6)
	3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm	2581 2581X	Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm cap-head machine (hex drive) (6)
062ED	NL (2) Stooring blocks 6064 T6 aluminum (red anadized) left 8 right)	4858	Screws, 3x25mm countersunk machine (hex drive) (6)
9635R	Steering blocks, 6061-T6 aluminum (red-anodized), left & right)/ steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/	9682	Screws, 3x45mm cap-head machine (hex drive) (6)
	3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm	2550	Screws, 3x8mm countersunk machine (6) (hex drive)
0507	NL (2)	3937	Screws, 4x12mm button-head machine (hex drive) (6)
9537 9637X	Steering blocks, left & right/ 4x16mm BCS (4)/ M4x0.7 NL (4) Steering blocks, left & right/ steering block arms (aluminum,	2542 2546	Screws, 4x12mm countersunk machine (hex drive) (6) Screws, 4x15mm countersunk machine (hex drive) (6)
3031X	blue-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)	3933	Screws, 4x16mm button-head machine (hex drive) (6)
9637A	Steering blocks, left & right/ steering block arms (aluminum,	2589	Screws, 4x20mm button-head machine (hex drive) (6)
00070	dark titanium-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)	2596	Screws, 4x25mm button-head machine (hex drive) (6)
9637G	Steering blocks, left & right/ steering block arms (aluminum, green-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)	2595	Screws, 4x35mm button-head machine (hex drive) (6)
9637T	Steering blocks, left & right/ steering block arms (aluminum,	3939 1548	Screws, 4x6mm button-head machine (hex drive) (with threadlock) (6) Set (grub) screws, 3x4mm (8)/ 4x4mm (stainless) (4)
	orange-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)	9588	Shoulder screws, 3x16mm (2)
9637R	Steering blocks, left & right/ steering block arms (aluminum, red-	9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4),
9526	anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2) Steering link (30mm) (1)/ hollow balls (2)	0544	3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2)
9633	Suspension arm covers, black, front (left and right)/ 2.5x8 CCS (12)	9541 9542	Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2) Suspension pins, outer, front, 3.5x48.2mm (hardened steel) (2)/
9633X	Suspension arm covers, blue, front (left and right)/ 2.5x8 CCS		M3x0.5mm NL, flanged (2)
9633G	(12) Suspension arm covers, green, front (left and right)/ 2.5x8 CCS (12)	9543	Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/ M3x0.5mm NL, flanged (2)
9633T	Suspension arm covers, orange, front (left and right)/ 2.5x8 CCS		Motors & Electronics
9633R	(12) Suspension arm covers, red, front (left and right)/ 2.5x8 CCS (12)	3476 3475	Cooling fan kit (with shroud) (fits #3483 motor) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
9531	Suspension arm, front (left), black	9590	Gear adapter, fixed (A)/ motor mount spacer
9531X	Suspension arm, front (left), blue	2277	Gear set, metal (for 2275 servo)
9531G	Suspension arm, front (left), green	9591	Hardware, motor mount, Sledge®
9531T	Suspension arm, front (left), orange	9589	Motor mount, aluminum (upper and lower)/ motor mount spacer/
9531R 9530	Suspension arm, front (left), red Suspension arm, front (right), black	3483	hardware Motor, 2000Kv 77mm, brushless (with 6.5mm gold-plated connectors
9530X	Suspension arm, front (right), blue	0.00	& high-efficiency heatsink)
9530G	Suspension arm, front (right), green	3483R	Rebuild kit, 2000Kv motor, brushless (includes plastic endbell,
9530T	Suspension arm, front (right), orange		5x16x5mm ball bearings (2), 5.05x7.5x.05 washer (1),
9530R	Suspension arm, front (right), red		5.05x7.5x0.1 washer (1), 5.05x7.5x.19 washer (1), 6x5x8.5 spacer (1))
9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4), 3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2)	2278	Servo case, aluminum (black-anodized) (middle) (for 2275 servo)
9541	Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2)	2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2275
9542	Suspension pins, outer, front, 3.5x48.2mm (hardened steel) (2)/	2255	servo) Servo, digital high-torque 400 brushless, metal gear (ball
9595	M3x0.5mm NL, flanged (2) Sway bar kit, Sledge® (front and rear) (includes front and rear	2275	bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
9596	sway bars and linkage) Sway bar set, Sledge® (includes 1 each of all 6 sway bars)	3477	Shroud, motor fan (fits #3483 motor)
9527	Tie bars, front, 6061-T6 aluminum (blue-anodized)	3484	Velineon® VXL-6s Brushless Power System, waterproof (includes
9527A	Tie bars, front, 6061-T6 aluminum (dark titanium-anodized)	24057	VXL-6s ESC and 2000Kv, 77mm motor)
9527G	Tie bars, front, 6061-T6 aluminum (green-anodized)	3485T	Velineon® VXL-6s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
9527T	Tie bars, front, 6061-T6 aluminum (orange-anodized)	3478	Wire harness (for use with #3475 cooling fan)
9527R 9629	Tie bars, front, 6061-T6 aluminum (red-anodized) Tie bars, front, 7075-T6 aluminum (blue-anodized) (fits Sledge®)		Radio System, Batteries & Chargers
	Tie bars, front, 7075-16 aluminum (blue-anouzed) (fits Sieuge®) Tie bars, front, 7075-T6 aluminum (dark titanium-anodized) (fits	2872X	5000mah 11.1v 3-Cell 25C LiPo Battery
9629A		2842X	5000mah 7.4v 2-Cell 25C LiPo Battery
9629A	Sledge®) Tis here front 7075 T6 aluminum (green anadized) (fits		
	Sledge®) Tie bars, front, 7075-T6 aluminum (green-anodized) (fits Sledge®)	2843X	5800mah 7.4v 2-Cell 25C LiPo Battery 7600mah 7.4v 2-Cell 25C LiPo Battery
9629A	Tie bars, front, 7075-T6 aluminum (green-anodized) (fits Sledge®) Tie bars, front, 7075-T6 aluminum (orange-anodized) (fits	2843X 2869X 2914	7600mah 7.4v 2-Cell 25C LiPo Battery Battery, Power Cell AA Alkaline (4)
9629A 9629G 9629T	Tie bars, front, 7075-T6 aluminum (green-anodized) (fits Sledge®) Tie bars, front, 7075-T6 aluminum (orange-anodized) (fits Sledge®)	2843X 2869X 2914 1726	7600mah 7.4v 2-Cell 25C LiPo Battery Battery, Power Cell AA Alkaline (4) Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
9629A 9629G	Tie bars, front, 7075-T6 aluminum (green-anodized) (fits Sledge®) Tie bars, front, 7075-T6 aluminum (orange-anodized) (fits	2843X 2869X 2914	7600mah 7.4v 2-Cell 25C LiPo Battery Battery, Power Cell AA Alkaline (4)

Page 4	Sledge®: TQi Traxxas Link Enabled 2.4GHz Radio	& TSM (Model 95076-4) Parts List
2991	Battery/charger completer pack (includes #2972 Dual iD charger	9598	Linkage, sway bar (front or rear)
2990	(1), #2869X 7600mAh 7.4V 2-cell 25C LiPo iD® Battery (2)) Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2))	9597 9519X	Mounts, sway bar/ collars (front and rear) Mud guards, rear, blue (left and right)/ 3x15 CCS (2)/ 3x25 CCS
2998	Battery/charger completer pack (includes #2981 iD charger (1),	9519	(2) Mud guards, rear, gray (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2)
	#2890X 6700mAh 14.8V 4-cell 25C LiPo battery (1))	9519G	Mud guards, rear, green (left and right)/ 3x15 CCS (2)/ 3x25 CCS
2972	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification	9519T	(2) Mud guards, rear, orange (left and right)/ 3x15 CCS (2)/ 3x25 CCS
2973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification	95191 9519R	(2)
2970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery	9538	Mud guards, rear, red (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2) Shock tower, rear, 6061-T6 aluminum (blue-anodized)
	Identification	9538A	Shock tower, rear, 6061-T6 aluminum (gray-anodized)
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification	9538G	Shock tower, rear, 6061-T6 aluminum (green-anodized)
2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	9538T 9538R	Shock tower, rear, 6061-T6 aluminum (orange-anodized) Shock tower, rear, 6061-T6 aluminum (red-anodized)
	Battery Identification	9638	Shock tower, rear, 7075-T6 aluminum (blue-anodized) (fits
6525 6566	Communication link, telemetry expander Data link, telemetry expander (connects #6550X telemetry		Sledge®)
0000	expander 2.0 to the #3485 Velineon® VXL-6s or #3496 Velineon®	9638A	Shock tower, rear, 7075-T6 aluminum (dark titanium-anodized) (fits Sledge®)
0077	VXL-8s electronic speed control)	9638G	Shock tower, rear, 7075-T6 aluminum (green-anodized) (fits
2277 2968X	Gear set, metal (for 2275 servo) LiPo cell voltage checker/balancer (includes #2938X adapter for	осоот	Sledge®)
2968	Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for	9638T	Shock tower, rear, 7075-T6 aluminum (orange-anodized) (fits Sledge®)
	Traxxas® iD® batteries)	9638R	Shock tower, rear, 7075-T6 aluminum (red-anodized) (fits Sledge®)
6563 6535	Mount, telemetry expander (attaches to chassis brace (T-Bar)) Mount, temperature sensor (electric motors)/ wire tie/ thermal	9634	Suspension arm covers, black, rear (left and right)/ 2.5x8 CCS (12)
	pad	9634X 9634G	Suspension arm covers, blue, rear (left and right)/ 2.5x8 CCS (12) Suspension arm covers, green, rear (left and right)/ 2.5x8 CCS
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)	00040	(12)
6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)	9634T	Suspension arm covers, orange, rear (left and right)/ 2.5x8 CCS (12)
6526 6527	Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage	9634R	Suspension arm covers, red, rear (left and right)/ 2.5x8 CCS (12)
6521	Sensor, temperature and voltage (long)	9534 9534X	Suspension arm, rear (left), black Suspension arm, rear (left), blue
2278	Servo case, aluminum (black-anodized) (middle) (for 2275 servo)	9534G	Suspension arm, rear (left), green
2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2275 servo)	9534T	Suspension arm, rear (left), orange
2275	Servo, digital high-torque, metal gear (ball bearing), waterproof	9534R 9533	Suspension arm, rear (left), red
6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio system	9533X	Suspension arm, rear (right), black Suspension arm, rear (right), blue
6550X	Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module)	9533G	Suspension arm, rear (right), green
6551X	Telemetry GPS module 2.0, TQi radio system (for use only with	9533T	Suspension arm, rear (right), orange
	#6550X telemetry expander)	9533R 9540	Suspension arm, rear (right), red Suspension pin set, front & rear (hardened steel), 4x67mm (4),
6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)		3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2)
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro	9541 9543	Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2) Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/ M3x0.5mm NL, flanged (2)
6528	receiver) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-	9595	Sway bar kit, Sledge® (front and rear) (includes front and rear sway bars and linkage)
6529	channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-	9596	Sway bar set, Sledge® (includes 1 each of all 6 sway bars)
	channel (transmitter only)	9528	Tie bars, rear, 6061-T6 aluminum (blue-anodized)
6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-	9528A 9528G	Tie bars, rear, 6061-T6 aluminum (dark titanium-anodized) Tie bars, rear, 6061-T6 aluminum (green-anodized)
6511	channel (transmitter only) Traxxas® Link Bluetooth® module	9528T	Tie bars, rear, 6061-T6 aluminum (orange-anodized)
	Ready-To-Race Model	9528R	Tie bars, rear, 6061-T6 aluminum (red-anodized)
95076-4	Sledge®: 1/8 Scale 4WD Brushless Electric Monster Truck with TQi 2.4GHz Traxxas Link™ Enabled Radio System and Traxxas Stability	9630 9630A	Tie bars, rear, 7075-T6 aluminum (blue-anodized) (fits Sledge®) Tie bars, rear, 7075-T6 aluminum (dark titanium-anodized) (fits
	Management (TSM)®	9630G	Sledge®) Tie bars, rear, 7075-T6 aluminum (green-anodized) (fits Sledge®)
	Rear Suspension	9630T	Tie bars, rear, 7075-T6 aluminum (orange-anodized) (fits
9529	Bulkhead, front or rear	9630R	Sledge®) Tie bars, rear, 7075-T6 aluminum (red-anodized) (fits Sledge®)
9548 9548X	Camber links, rear (144mm) (2) (assembled with hollow balls) Camber links, rear, Sledge® (TUBES blue-anodized, 7075-T6	9596	Wires, sway bar (front or rear) (6)
00-1070	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm		Shock Oil
	(1)	5031 5032	Oil, shock (20 wt, 200 cSt, 60cc) (silicone) Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
9548A	Camber links, rear, Sledge® (TUBES dark titanium-anodized,	5032	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
	7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench,	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
	8mm (1)	5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
9548G	Camber links, rear, Sledge® (TUBES green-anodized, 7075-T6	5036 5037	Oil, shock (70 wt, 900 cSt, 60cc) (silicone) Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm	5029	Shock oil bottle (60cc) (for mixing shock oil)
	(1)	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &
9548T	Camber links, rear, Sledge® (TUBES orange-anodized, 7075-T6	5038	80 wt premium shock oils with spinning carousel rack) Spinning carousel rack
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm	0000	Shocks (GT-Maxx®)
9548R	(1) Camber links, rear, Sledge® (TUBES red-anodized, 7075-T6	8965X	Body, GT-Maxx® shock (aluminum, blue-anodized) (1)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,	9665X	Body, GT-Maxx® shock (aluminum, blue-anodized) (long) (1)
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)	8965G 9665G	Body, GT-Maxx® shock (aluminum, green-anodized) (1) Body, GT-Maxx® shock (aluminum, green-anodized) (long) (1)
9683	Hollow balls, steel (8)	8965T	Body, GT-Maxx® shock (aluminum, orange-anodized) (1)

Page 5	Sledge®: TQi Traxxas Link Enabled 2.4GHz Radio	& TSM (Model 95076-4) Parts List
9665T 8965R	Body, GT-Maxx® shock (aluminum, orange-anodized) (long) (1) Body, GT-Maxx® shock (aluminum, red-anodized) (1)	2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2275 servo)
9665R	Body, GT-Maxx® shock (aluminum, red-anodized) (long) (1)	9544	Servo horn, steering, metal
8962	Rebuild kit, GT-Maxx® shocks (lower cartridge, pistons, piston nuts, bladders, screws) (renews 2 shocks)	9545A	Servo saver post/ adjuster nut/ locknut (dark titanium-anodized, 6061-T6 aluminum) (1 each)
9664A	Shock caps, aluminum (black-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge®)	9545G	Servo saver post/ adjuster nut/ locknut (green-anodized, 6061-T6 aluminum) (1 each)
9664X	Shock caps, aluminum (blue-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge®)	9545T	Servo saver post/ adjuster nut/ locknut (orange-anodized, 6061- T6 aluminum) (1 each)
9664G	Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge®)	9545R	Servo saver post/ adjuster nut/ locknut (red-anodized, 6061-T6 aluminum) (1 each)
9664T	Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge®)	9545 2255	Servo saver/ servo saver spring/ servo horn, steering (assembled) Servo, digital high-torque 400 brushless, metal gear (ball
9664R	Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge®)	2275	bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
9664	Shock caps, GT-Maxx® shocks (2)/ spring perch/ adjusters (2) (for 2 shocks)	9636X	Steering block arms (aluminum, blue-anodized) (2) (fits #9635 series & 9637 series steering blocks)
9663	Shock pins, hardened steel (front (2), rear (2))/ 2.5x8mm CCS (4)	9636A	Steering block arms (aluminum, dark titanium-anodized) (2) (fits
8963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends		#9635 series & 9637 series steering blocks)
8963T	(2)/ hollow balls (2) Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with	9636G	Steering block arms (aluminum, green-anodized) (2) (fits #9635 series & 9637 series steering blocks
9662	rod ends and steel hollow balls) Shock shaft, 80mm (GT-Maxx®) (steel, chrome finish) (2) (assembled	9636T	Steering block arms (aluminum, orange-anodized) (2) (fits #9635 series & 9637 series steering blocks)
9662T	with rod ends and steel hollow balls) Shock shaft, 80mm (GT-Maxx®) (TiN-coated) (2) (assembled with	9636R	Steering block arms (aluminum, red-anodized) (2) (fits #9635 series & 9637 series steering blocks)
90021	rod ends and steel hollow balls)	9635X	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right/
9660	Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)		steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/ 3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm
9661	Shocks, GT-Maxx®, long, aluminum (blue-anodized) (fully assembled w/o springs) (2)	9635A	NL (2) Steering blocks, 6061-T6 aluminum (dark titanium-anodized), left
8968X	Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring		& right/ steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/ 3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/
8968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)	9635G	M3x0.5mm NL (2) Steering blocks, 6061-T6 aluminum (green-anodized), left & right/
8968A	Spring retainer (adjuster), orange-anodized aluminum, GT- Maxx® shocks (4) (assembled with o-ring)		steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/ 3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm
8968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)	9635T	NL (2) Steering blocks, 6061-T6 aluminum (orange-anodized), left & right/ steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/
8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)		3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm
8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)		NL (2)
9659 9658	Springs, shock (natural finish) (GT-Maxx®) (1.487 rate) (85mm) (2) Springs, shock (natural finish) (GT-Maxx®) (1.569 rate) (85mm) (2)	9635R	Steering blocks, 6061-T6 aluminum (red-anodized), left & right)/ steering block arms (2)/ 4x16mm BCS (with threadlock) (4)/
9657	Springs, shock (natural finish) (GT-Maxx®) (1.671 rate) (85mm) (2)	0527	3x18mm CS (2)/ 3x10mm BCS (with threadlock) (4)/ M3x0.5mm NL (2)
8969	Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)	9537 9637X	Steering blocks, left & right/ 4x16mm BCS (4)/ M4x0.7 NL (4) Steering blocks, left & right/ steering block arms (aluminum,
	Springs	3031 X	blue-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)
8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)	9637A	Steering blocks, left & right/ steering block arms (aluminum,
8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)		dark titanium-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)
9659	Springs, shock (natural finish) (GT-Maxx®) (1.487 rate) (85mm) (2)	9637G	Steering blocks, left & right/ steering block arms (aluminum,
9658	Springs, shock (natural finish) (GT-Maxx®) (1.569 rate) (85mm) (2)	9637T	green-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2) Steering blocks, left & right/ steering block arms (aluminum,
9657	Springs, shock (natural finish) (GT-Maxx®) (1.671 rate) (85mm) (2)	9637R	orange-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2) Steering blocks, left & right/steering block arms (aluminum, red-
8969	Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)	9526	anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2) Steering link (30mm) (1)/ hollow balls (2)
	Spur Gears & Pinion Gears	9549	Toe links, front (120mm) (2) (assembled with hollow balls)
9590 6482X	Gear adapter, fixed (A)/ motor mount spacer Gear, 12-T pinion (machined, hardened steel) (1.0 metric pitch)	9549X	Toe links, Sledge® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (120mm) (2)/ rod ends, assembled with
6483X	(fits 5mm shaft)/ set screw Gear, 13-T pinion (machined, hardened steel) (1.0 metric pitch) (fits	9549A	steel hollow balls (4)/ aluminum wrench, 8mm (1) Toe links, Sledge® (TUBES dark titanium-anodized, 7075-T6
6489X	Smm shaft)/ set screw Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw		aluminum, stronger than titanium) (120mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm
6491R	(for use only with steel spur gears) Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/	9549G	(1) Toe links, Sledge® (TUBES green-anodized, 7075-T6 aluminum,
9651	set screw (for use only with steel spur gears) Spur gear, 46-tooth, steel (1.0 metric pitch)		stronger than titanium) (120mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)
9652	Spur gear, 52-tooth, steel (1.0 metric pitch)	9549T	Toe links, Sledge® (TUBES orange-anodized, 7075-T6 aluminum,
	Steering Components		stronger than titanium) (120mm) (2)/ rod ends, assembled with
9525	- -	9549R	steel hollow balls (4)/ aluminum wrench, 8mm (1) Toe links, Sledge® (TUBES red-anodized, 7075-T6 aluminum,
9525 9546A	Bellcrank posts, steering (aluminum, blue-anodized) Draglink, steering, 6061-T6 aluminum (dark titanium-anodized)/ 3x14mm SS (2)	JUTUR	stronger than titanium) (120mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)
9546G	Draglink, steering, 6061-T6 aluminum (green-anodized)/ 3x14mm SS (2)		Suspension Linkage
9546T	Draglink, steering, 6061-T6 aluminum (orange-anodized)/ 3x14mm SS (2)	9547 9547X	Camber links, front (117mm) (2) (assembled with hollow balls) Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6
9546R	Draglink, steering, 6061-T6 aluminum (red-anodized)/ 3x14mm SS (2)		aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm
9546	Draglink, steering/ 3x14mm SS (2)	9547A	(1) Camber links, front, Sledge® (TUBES dark titanium-anodized,
2277	Gear set, metal (for 2275 servo)	JUTIA	7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
9683	Hollow balls, steel (8)		ends, assembled with steel hollow balls (4)/ aluminum wrench,
2278	Servo case, aluminum (black-anodized) (middle) (for 2275 servo)		8mm (1)

Page 6	Sledge®: TQi Traxxas Link Enabled 2.4GHz Radio	& TSM (N	Model 95076-4) Parts List
9547G	Camber links, front, Sledge® (TUBES green-anodized, 7075-T6	5171	Tires, Maxx® Chevron 3.8" (2) (fits Revo®/T-Maxx®/E-Maxx)
	aluminum, stronger than titanium) (117mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm	8673 5375	Tires, paddle 3.8" (2)/ foam inserts (2) Tires, Response Pro 3.8" (soft-compound, narrow profile, short
9547T	(1) Camber links, front, Sledge® (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends,	5471	knobby design)/ foam inserts (2) Tires, Response racing 3.8" (soft-compound, narrow profile,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm	9670	short knobby design)/ foam inserts (2) Tires, Sledgehammer® (2)/ foam inserts (2)
	(1)	5470	Tires, SportTraxx racing 3.8" (soft compound, directional and
9547R	Camber links, front, Sledge® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod ends,		assymetrical tread design)/ foam inserts (2)
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm	5171	Tires, T-Maxx® 3.8" (2) (fits Revo®/Maxx® series)
	(1)	8670 9569	Tires, Talon EXT 3.8" (2), foam inserts (2) Wheel covers, black (4) (fits #9572 wheels)
9548	Camber links, rear (144mm) (2) (assembled with hollow balls)	9568T	Wheel covers, black chrome (4) (fits #9572 wheels)
9548X	Camber links, rear, Sledge® (TUBES blue-anodized, 7075-T6	9569X	Wheel covers, blue (4) (fits #9572 wheels)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm	9569A	Wheel covers, gray (4) (fits #9572 wheels)
	(1)	9569G	Wheel covers, green (4) (fits #9572 wheels)
9548A	Camber links, rear, Sledge® (TUBES dark titanium-anodized,	9569T	Wheel covers, orange (4) (fits #9572 wheels)
	7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod	9569R 9568A	Wheel covers, red (4) (fits #9572 wheels)
	ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)	9568X	Wheel covers, satin black chrome (4) (fits #9572 wheels) Wheel covers, satin chrome (4) (fits #9572 wheels)
9548G	Camber links, rear, Sledge® (TUBES green-anodized, 7075-T6	9567	Wheel hubs, +5 mm (4), +10 mm (4) (fits #9572 wheels)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 8mm	8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
05407	(1)	8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4),
9548T	Camber links, rear, Sledge® (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends,	8654A	3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)	8654R	(4)/ 3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4),
9548R	Camber links, rear, Sledge® (TUBES red-anodized, 7075-T6	•••	3x14mm pin (4)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,	7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm (1)	7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
9546A	Draglink, steering, 6061-T6 aluminum (dark titanium-anodized)/	7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
	3x14mm SS (2)	7758T 7758R	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4) Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
9546G	Draglink, steering, 6061-T6 aluminum (green-anodized)/ 3x14mm	8671	Wheels, 3.8" (black) (2) (17mm splined)
OF46T	SS (2)	9671	Wheels, 3.8" (black) (2) (17mm splined)
9546T	Draglink, steering, 6061-T6 aluminum (orange-anodized)/ 3x14mm SS (2)	8671G	Wheels, 3.8" (green) (2) (17mm splined)
9546R	Draglink, steering, 6061-T6 aluminum (red-anodized)/ 3x14mm	8671A	Wheels, 3.8" (orange) (2) (17mm splined)
	SS (2)		Traxxas Tools
9546	Draglink, steering/ 3x14mm SS (2)	3433X	Body reamer (aluminum handle)
9683 9544	Hollow balls, steel (8) Servo horn, steering, metal	3433	Body reamer (plastic handle)
9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4),	3436 3432	Cap, body reamer Scissors, curved tip
	3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2)	3431	Scissors, straight tip
9541	Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2)	8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
9542 9543	Suspension pins, outer, front, 3.5x48.2mm (hardened steel) (2)/ M3x0.5mm NL, flanged (2) Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/		premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
9545	M3x0.5mm NL, flanged (2)	8720	and 8.0mm), 1/4" drive
9549	Toe links, front (120mm) (2) (assembled with hollow balls)	8720 8721	Speed bit handle, large (overmolded) Speed bit handle, medium (one piece)
	Team Traxxas Items	8722	Speed bit handle, premium (rubber overmold)
2514	Decal sheet, racing sponsors	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)		premium handle (medium), travel pouch, hex drivers (straight:
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm,
9909	Traxxas® racing banner, red & black (3x7 feet)		8.0mm), 1/4" drive
	Tires & Wheels	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
8674	Tires & wheels, assembled, glued (black 3.8" wheels, paddle tires, foam inserts) (2) (TSM® rated)		includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
8672	Tires & wheels, assembled, glued (black wheels, Talon EXT tires,	8719	2.5mm, 3.0mm), 1/4" drive Speed Bit Master Set, nut driver, 6-piece, includes premium
96726	foam inserts) (2) (17mm splined) (TSM® rated)	0713	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
8672G	Tires & wheels, assembled, glued (green wheels, Talon EXT tires, foam inserts) (2) (17mm splined) (TSM® rated)		5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8672A	Tires & wheels, assembled, glued (orange wheels, Talon EXT	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
	tires, foam inserts) (2) (17mm splined) (TSM® rated)	8716X	drive Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
9572T	Tires and wheels, assembled, glued (3.8" black chrome wheels, black chrome wheel covers, Sledgehammer® tires, foam inserts)	8715	3.0mm) 1/4" drive Speed Bit Set, hex driver, 3-piece ban-end (2.5mm, 2.5mm, Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
9572	(2) Tires and wheels, assembled, glued (3.8" black wheels, gray	J	2.5mm), 1/4" drive
331 Z	wheel covers, Sledgehammer® tires, foam inserts) (2)	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
9672	Tires and wheels, assembled, glued (3.8" black wheels,	07.105	2.5mm, 3.0mm), 1/4" drive
	Sledgehammer® tires, foam inserts) (2)	2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint
	, , ,		
9572A	Tires and wheels, assembled, glued (3.8" satin black chrome wheels, satin black chrome wheel covers, Sledgehammer® tires,	3415	wrench) Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm
	Tires and wheels, assembled, glued (3.8" satin black chrome wheels, satin black chrome wheel covers, Sledgehammer® tires, foam inserts) (2)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
9572A 9572X	Tires and wheels, assembled, glued (3.8" satin black chrome wheels, satin black chrome wheel covers, Sledgehammer® tires, foam inserts) (2) Tires and wheels, assembled, glued (3.8" satin chrome wheels, satin chrome wheel covers, Sledgehammer® tires, foam inserts)	3415	•
9572X	Tires and wheels, assembled, glued (3.8" satin black chrome wheels, satin black chrome wheel covers, Sledgehammer® tires, foam inserts) (2) Tires and wheels, assembled, glued (3.8" satin chrome wheels, satin chrome wheel covers, Sledgehammer® tires, foam inserts) (2)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
	Tires and wheels, assembled, glued (3.8" satin black chrome wheels, satin black chrome wheel covers, Sledgehammer® tires, foam inserts) (2) Tires and wheels, assembled, glued (3.8" satin chrome wheels, satin chrome wheel covers, Sledgehammer® tires, foam inserts)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm

Page 7 Sledge®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 95076-4) Parts List

	Turnbuckles & Threaded Rods
9547	Camber links, front (117mm) (2) (assembled with hollow balls)
9547X	Camber links, front, Sledge® (TUBES blue-anodized, 7075-T6
3347X	aluminum, stronger than titanium) (117mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9547A	Camber links, front, Sledge® (TUBES dark titanium-anodized,
004174	7075-T6 aluminum, stronger than titanium) (117mm) (2)/ rod
	ends, assembled with steel hollow balls (4)/ aluminum wrench,
	8mm (1)
9547G	Camber links, front, Sledge® (TUBES green-anodized, 7075-T6
	aluminum, stronger than titanium) (117mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9547T	Camber links, front, Sledge® (TUBES orange-anodized, 7075-T6
	aluminum, stronger than titanium) (117mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9547R	Camber links, front, Sledge® (TUBES red-anodized, 7075-T6
	aluminum, stronger than titanium) (117mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9548	Camber links, rear (144mm) (2) (assembled with hollow balls)
9548X	Camber links, rear, Sledge® (TUBES blue-anodized, 7075-T6
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
9548A	(1) Combon links, room Sladge® (TUPES dark titanium anadized
9340A	Camber links, rear, Sledge® (TUBES dark titanium-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod
	ends, assembled with steel hollow balls (4)/ aluminum wrench,
	8mm (1)
9548G	Camber links, rear, Sledge® (TUBES green-anodized, 7075-T6
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9548T	Camber links, rear, Sledge® (TUBES orange-anodized, 7075-T6
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9548R	Camber links, rear, Sledge® (TUBES red-anodized, 7075-T6
	aluminum, stronger than titanium) (144mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
	(1)
9683	Hollow balls, steel (8)
9549	Toe links, front (120mm) (2) (assembled with hollow balls)
9549X	Toe links, Sledge® (TUBES blue-anodized, 7075-T6 aluminum,
	stronger than titanium) (120mm) (2)/ rod ends, assembled with
	steel hollow balls (4)/ aluminum wrench, 8mm (1)
9549A	Toe links, Sledge® (TUBES dark titanium-anodized, 7075-T6
	aluminum, stronger than titanium) (120mm) (2)/ rod ends,
	assembled with steel hollow balls (4)/ aluminum wrench, 8mm
05400	(1)
9549G	Toe links, Sledge® (TUBES green-anodized, 7075-T6 aluminum,
	stronger than titanium) (120mm) (2)/ rod ends, assembled with
9549T	steel hollow balls (4)/ aluminum wrench, 8mm (1) Toe links, Sledge® (TUBES orange-anodized, 7075-T6 aluminum,
3343 I	stronger than titanium) (120mm) (2)/ rod ends, assembled with
	steel hollow balls (4)/ aluminum wrench, 8mm (1)
9549R	Toe links, Sledge® (TUBES red-anodized, 7075-T6 aluminum,
307311	stronger than titanium) (120mm) (2)/ rod ends, assembled with
	steel hollow balls (4)/ aluminum wrench, 8mm (1)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM